

26,4 cm (10,4") to 48,3 cm (19") 4:3 Industrial Monitor VESA Chassis

- Compact design
- Sturdy steel sheet housing
- Installation with rear VESA mounting interface
- Resistive touch screen optional



LCDS	26,4 CM (10,4") 4:3	30,7 CM (12,1") 4:3	38,1 CM (15") 4:3
Model Name	WM 10-V-CH	WM 12-V-CH	WM 15-VDP-CH
Resolution	800 × 600	800 × 600	1024 × 768
Backlight	LED	LED	LED
Brightness (typ.)	600 cd/m ²	450 cd/m ²	250 cd/m ²
Contrast Ratio (typ.)	400 : 1	700 : 1	700 : 1
Viewing Angle H / V (typ.)	-70°~70° / -70°~60°	-80°~80° / -75°~65°	-80°~80° / -70°~70°
Power Consumption (typ.)	13 W	15 W	25 W
Dimensions (W × H × D)	260 × 215 × 35 mm	290 × 230 × 45 mm	358 × 292 × 48 mm

LCDS	43,2 CM (17") 4:3	48,3 CM (19") 4:3
Model Name	WM 17-VDP-CH	WM 19-VDP-CH
Resolution	1280 × 1024	1280 × 1024
Backlight	LED	LED
Brightness (typ.)	350 cd/m ²	250 cd/m ²
Contrast Ratio (typ.)	1000 : 1	1000 : 1
Viewing Angle H / V (typ.)	-85°~85° / -80°~80°	-85°~85° / -80°~80°
Power Consumption (typ.)	32 W	33 W
Dimensions (W × H × D)	410 × 330 × 58 mm	445 × 355 × 55 mm

GENERAL DATA

Touchscreen	optional	ELO resistive (RS-232C or USB)
	optional	Premier resistive (RS-232C or USB)
Power input		12 V _{DC}
	optional	9~36 V _{DC}
Power supply	incl.	external, 100~240 V _{AC}
Power management		VESA DPMS compliant
Plug and Play		VESA DDC 1/2B
Operating temperature		0~50 °C

SIGNAL INPUT

VGA		1 × 15-pin D-sub
DVI	≥ WM 15	1 × DVI
Video	≤ WM 12 optional	1 × Composite (PAL/NTSC)
	≥ WM 15 incl.	1 × Composite (PAL/NTSC)

CONSTRUCTION

Material		sturdy steel sheet
Color		black
	on request	customized
Mounting		VESA 75 × 75 mm
	WM 19	VESA 100 × 100 mm