

19-inch / 1U Rackmount

- Various keyboard layouts
- 16 mm trackball
- Robust and durable
- Perfect workmanship and high-quality materials guarantee a rugged and durable input device.
- While opening the front hood the spring mounted keyboard moves some centimeters towards the user and can be extracted comfortably until it locks.
- The front hood arrests after closing in a spring-ball-catch – material fatigue impossible.



GENERAL DATA

Keyboard type	Cherry G84-4400
MCBF	> 1 billion operations (mean cycles between failur)
Keyboard layout	DE Germany, 84-key EU International incl. "€", 83-key US US-Engl., 83-key GB UK-Engl., 84-key IT Italy, 84-key ... further variants on request
Trackball	16 mm trackball, 2 mouse keys
Power consumption	USB max. 100 mA PS/2 max. 32 mA keyboard typ. 5 mA trackball
Operating temperature	0°–50° C

INTERFACES

2 × PS/2 or USB	Keyboard Trackball
Contacts	Gold crosspoint contacts

CONSTRUCTION

Dimensions	width front	483 mm
	width corpus	383 mm
	installation depth	220,5 mm
	height	43,6 mm
Material	front hood	steel sheet, RAL 7035
	front frame	aluminium, RAL 7035
	corpus	stainless steel
	keyboard holder	aluminium
Cable lengths		175 cm