

54,6 cm (21,5") bis 69 cm (27") 16:9 Industrie-Monitor Einbau



- Robuste Stahlblech-Mechanik
- Montage als Openframe oder mit Frontplatte
- Resistiver Touch-Screen optional

LCDS	54,6 CM (21,5") 16:9	60,5 CM (23,8") 16:9	69 CM (27") 16:9
Model Name	WM 22W-VDP-OF	WM 24W-VDP-OF	WM 27W-VDP-OF
Resolution	1920 x 1080	1920 x 1080	1920 x 1080
Brightness (typ.)	250 cd/m ²	250 cd/m ²	300 cd/m ²
Contrast Ratio (typ.)	1000 : 1	3000 : 1	3000 : 1
Viewing Angle H / V (typ.)	-85°~85° / -80°~80°	-89°~89° / -89°~89°	-89°~89° / -89°~89°
Backlight	LED	LED	LED
Power Consumption (typ.)	40 W	40 W	45 W
Dimensions (W x H x D)	504 x 318 x 60 mm	577 x 344 x 58 mm	689 x 427 x 56 mm

GENERAL DATA

Touchscreen	≤ 24W optional resistive (RS-232C or USB)
Power input	12 V _{DC}
	optional 9~36 V _{DC}
Power supply	incl. external, 100~240 V _{AC}
Power management	VESA DPMS compliant
Plug and Play	VESA DDC 1/2B
Operating temperature	0°~50° C

SIGNAL INPUT

VGA	1 x 15-pin D-sub
DVI	1 x DVI
Video	1 x Composite (PAL / NTSC)

MECHANIK

Material	robustes Stahlblech (verzinkt)
Montage	Openframe-Einbau
	VESA 75 x 75 mm
	VESA 100 x 100 mm
	≥ 24W VESA 200 x 100 mm zusätzlich
optional	Panelmount-Front (IP65)