

## 81 cm (32") bis 107 cm (42") 16:9 Industrie-Monitor Einbau



- Robuste Stahlblech-Mechanik
- Montage als Openframe-Gerät
- Touch-Screen (SAW) optional

LCDS	81 CM (32") 16:9	107 CM (42") 16:9
Model Name	WM 32W-VDP-OF	WM 42W-VDP-OF
Resolution	1920 x 1080	1920 x 1080
Brightness (typ.)	350 cd/m <sup>2</sup>	500 cd/m <sup>2</sup>
Contrast Ratio (typ.)	3000 : 1	2500 : 1
Viewing Angle H / V (typ.)	-89°~89° / -89°~89°	-89°~89° / -89°~89°
Backlight	LED	LED
Power Consumption (typ.)	75 W	180 W
Dimensions (W x H x D)	800 x 480 x 68 mm	1024 x 617 x 130 mm

GENERAL DATA	
Touchscreen	optional SAW (RS-232C or USB)
Power input	WM 32W 24 V <sub>DC</sub> WM 42W 110~240 V <sub>AC</sub>
Power supply	WM 32W external, 110~240 V <sub>AC</sub> (incl.) WM 42W internal
Power management	VESA DPMS compliant
Plug and Play	VESA DDC 1/2B
Operating temperature	0°~50° C

SIGNAL INPUT	
VGA	1 x 15-pin D-sub
DVI	1 x DVI-D
Video	1 x Composite (PAL / NTSC)

MECHANIK	
Material	robustes Stahlblech (verzinkt)
Montage	Openframe-Einbau VESA 100 x 100 mm VESA 200 x 100 mm