

25,7 cm (10,1") 16:10 Industrie-Tablet-PC Intel® Core™ i5 (5th Gen. / Broadwell)

- **Typenbezeichnung: M101H**
- IP65 wasser- und staubdicht
- Schock-, Vibrations- und Sturz-Resistenz (MIL-STD-810G)
- 1920 x 1200 PCAP Multi-Touch
- Windows Betriebssysteme
- WLAN, Bluetooth, GPS
- optional 1D/2D Barcodereader
- 5 MP Main- / 2 MP Web-Cam
- 5140 oder 10280 mAh Akku (hot-swappable)
- 2 programmierbare Tasten
- Aluminium-Gehäuse



SYSTEM

CPU (Intel® Mobile)	Core™ i5-5200U (2 x 2,2 GHz) (5 th Generation / Broadwell)
System memory	4 GB (max. 8 GB) DDR3L-1600
Solid-state drive	64 GB (max. 256 GB) mSATA MLC
Operating systems	Windows 7 Pro for Embedded Systems Windows Embedded Std. 7 (WS7P) Windows Embedded 8.1 Industry Pro Windows 10 IoT Enterprise

POWER

Battery	5140 mAh Li-poly battery, 7,4 V optional 10280 mAh Li-poly battery, 7,4 V optional hot-swappable (internal extra battery)
Battery life (max.)	8 h, optional 16 h (measured at dimming brightness, varies depending on usage conditions or attached external devices)
Power input	12~19 V _{DC}
Power supply	external, 100–240 V _{AC} (incl.)

WIRELESS COMMUNICATION

WLAN	IEEE 802.11a/b/g/n
Bluetooth	4.0 + Class 1
GPS	U-Blox Neo-6Q
WWAN	on request

DATA CAPTURE

Main camera (rear side)	5 MP, autofocus, 1 W LED flash
Webcam (front side)	2 MP
Barcode	optional 1D/2D barcode reader

INTERFACES (BEHIND RUBBER PROTECTOR)

30-pin combo connector	RJ-45 or RS-232
USB	1 x USB 3.0
Card slot	1 x Micro SD
Graphic	1 x Micro HDMI
Audio combo connector	line-out or mic-in

LCD

25,7 cm (10,1") 16:10 Touchscreen	1920 x 1200 (700 cd/m ² , 800:1) Projected capacitive multi-touch, min. 4-point
--------------------------------------	--

CONSTRUCTION

Dimensions (W x H x D)	272 x 198 x 21 mm
Weight	1,25 kg / 1,45 kg (high cap. battery)
Material	aluminium

CONTROLS, SENSORS, AUDIO, I/O

Control buttons	power, home, volume +/-, 2 x function key (user-defined)
Control LEDs	power, battery, HDD, RF
Sensors	light sensor, G sensor, gyrometer, e-compass
Audio	2 x 1 W speaker (rear side), built-in microphone (front side)
Touch pen	capacitive stylus

QUALITY / TESTS

Operating temperature	-20° C to 60° C (AC mode) -10° C to 50° C (battery mode)
Operating humidity	10% to 90%, non condensing
Ingress protection	IP65
Shock	MIL-STD-810G M. 516.6, Procedure I
Vibration	MIL-STD-810G M. 514.6, Procedure I
Drop (free to concrete)	MIL-STD-810G M. 516.6 (4 feet)
Certifications	CE, FCC
Warranty	24 months

ACCESSORIES (OPTIONAL)

- 30-pin connector cables: RJ-45 or RS-232
- Docking stations: office docking station, vehicle docking station
- VESA mounting kit
- Power: car power charger, high capacity battery
- Hand and shoulder straps, carry bag

