

## 20,3 cm (8") Vehicle Mounted Computer Intel® Atom™ E3845 (Bay Trail)

- Bereit für Fahrzeug- / Gabelstapler-Einbau (10–60 V<sub>DC</sub> Eingang, erweiterter Temperaturbereich, Montagezubehör etc.)
- Vor Ort wechselbare Fronteinheit (reduziert Serviceaufwand und Ausfallzeiten)
- Schutz gegen Staub und Wasser (IP65)
- Schock- / vibrationsfestes Gehäuse aus Magnesium-Legierung (MIL-STD-810G)
- Windows 10 IoT / 8.1 / 7
- WLAN, Bluetooth, GPS, optional 3G / 4G
- SMA-Anschluss für externe Antenne
- Kratzfester resistiver Touch (Finger & Stift)



Computer-Einheit mit QWERTY-Tastatur, 10 programmierbaren Funktionstasten und Ziffernblock



Computer + Docking



Docking



### SYSTEM

CPU (Intel® Mobile)	Atom™ E3845 (4 × 1,91 GHz)
System memory	4 GB (max. 8 GB) DDR3L-1600
Solid-state drive	64 GB (max. 256 GB) M.2 MLC
Operating systems	Windows 7 Pro for Embedded Systems Windows Embedded Std. 7 (WS7P) Windows Embedded Compact 7 (CE) Windows Embedded 8.1 Industry Pro Windows 10 IoT Enterprise

### POWER

Battery	3800 mAh Li-polymer 7,4 V (2S1P)
Power input	Computer 12 V <sub>DC</sub> Docking 10–60 V <sub>DC</sub> with isolation power and ignition control

### WIRELESS COMMUNICATION

WLAN	IEEE 802.11 a/b/g/n/ac
Bluetooth	Bluetooth 4.0
GPS	U-Blox Neo-6Q (at the docking)
WWAN	optional 4G (LTE, HSPA+, GSM/GPRS/EDGE, EV-DO Rev A, 1xRTT) or Optional 3G (HSPA+, GSM/GPRS/EDGE)

### INTERFACES COMPUTER

USB	1 × USB 3.0
Card slots	1 × SD, 1 × SIM

### INTERFACES DOCKING

Serial	COM1, COM2
USB	1 × USB 2.0
LAN port (PoE)	1 × 400 Mbps LAN port PoE as a Power sourcing equipment (PSE) support 802.3at Type 2
CANBUS / AUDIO	1 × CANBUS / AUDIO
SMA connector	for external antenna (WLAN, GPS, WWAN (optional))

### LCD

20,3 cm (8") 16:9	1024 × 480 (500 cd/m <sup>2</sup> )
Viewing angle	–80~80 ° / –80~80 ° (H / V)
Touchscreen	Anti scratch resistive touch and support for finger touch and stylus

### DATA CAPTURE

Camera	front side	2 MP (Win. 7 Pro / 8.1 / 10 IoT only)
--------	------------	---------------------------------------

### CONTROLS, SENSORS, AUDIO, I/O

Control buttons	Power, 10 × function key (F1–F10 user programmable)
LED indicators	Power, WLAN, Bluetooth, battery, HDD, blanking, heater
Reading light	bottom side (at the docking)
Light sensor	front side
Audio	2 × 3 W speaker (at the docking) 2 × microphone
Touch pen	Stylus kit

### CONSTRUCTION

Dimensions (W × H × D)	268 × 214 × 32 mm (computer) 202 × 245 × 52 mm (docking)
Weight	1,6 kg (computer) + 1,6 kg (docking)
Material	Magnesium alloy
Mounting	VESA 75 × 75 / 100 × 100 mm optional RAM mounting kit
Security	Key lock + release latch (docking), Kensington lock (computer)
Cooling	fanless

### QUALITY / TESTS

Operating temperature	–30 °C to 50 °C
Operating humidity	5 % to 95 % RH, non-condensing
Ingress protection	IP65
Shock	MIL-STD-810G M. 516.6, Procedure I
Vibration	MIL-STD-810G M. 514.6, Procedure I
Warranty	24 months

Version 170531

Irrtümer und Änderungen vorbehalten